

RACCORDI A SALDARE WELDING FITTINGS

CURVA A 45° PN25


45° ELBOW PN25




ARTICOLO	MISURE mm	BUTT WELDING - SDR 11	
CODE	SIZES mm		
CUQ 20	20 x 20	CUQ 160T	160 x 160
CUQ 25	25 x 25	CUQ 200T	200 x 200
CUQ 32	32 x 32	CUQ 250T	250 x 250
CUQ 40	40 x 40	CUQ 315T	315 x 315
CUQ 50	50 x 50		
CUQ 63	63 x 63		
CUQ 75	75 x 75		
CUQ 90	90 x 90		
CUQ 110	110 x 110		
CUQ 125	125 x 125		
CUQ 160	160 x 160		

SPECIFICHE TECNICHE

TECHNICAL SPECIFICATIONS



CODE	d	D	z	l	weight (g)
CUQ 20	20	28,2	16	24	11
CUQ 25	25	35,2	17	25	18
CUQ 32	32	45	20	32	38
CUQ 40	40	56,2	22	40	64
CUQ 50	50	70,2	25	48	116
CUQ 63	63	88,4	28	59	220
CUQ 75	75	105,2	31	66	292
CUQ 90	90	126,2	33	78	412
CUQ 110	110	154,2	42	90	904
CUQ 125	125	175,2	43	110	1044
CUQ 160	160	222,2	45	130	1786



BUTT WELDING - SDR 11						
CODE	DE	Z	H	H ₁	S	weight (g)
CUQ 160T	160	175	107	359	14,6	2450
CUQ 200T	200	190	118	392,5	18,2	4000
CUQ 250T	250	215	130	490,5	22,7	7000
CUQ 315T	315	280	180	400	30	20000

Tutti i raccordi TORO 25 sono compatibili con tutte le serie di tubi TORO 25.
All TORO 25 pipe fittings are compatible with all TORO 25 pipe series.

NSF 61 approved

STANDARD:

- ISO 15874
- ISO 15494
- DIN 8077-78