


ACCESORIOS CON ROSCA

THREADED FITTINGS

REDUCCIÓN CON ROSCA HEMBRA PN25


THREADED COUPLING PN25 - FEMALE




ARTÍCULO	MEDIDAS mm
CODE	SIZES mm
RFF 2020	20 x 1/2"
RFF 2025	20 x 3/4"
RFF 2520	25 x 1/2"
RFF 2525	25 x 3/4"
RFF 3225	32 x 3/4"
RFF 3232	32 x 1"
RFF 4040	40 x 1"1/4"
RFF 5050	50 x 1"1/2"
RFF 6363	63 x 2"
RFF 7575	75 x 2"1/2"
RFF 9090	90 x 3"
RFF 110110	110 x 4"

ESPECIFICACIONES TÉCNICAS

TECHNICAL SPECIFICATIONS



ARTÍCULO	d	Rp	D	D ₁	D ₂	D ₃	I ₁	I ₂	I ₃	I ₄	PESO (g)
RFF 2020	20	1/2"	30	36	40	35	11	14	7	10	60
RFF 2025	20	3/4"	30	42	47	43	11	14	7	9	76
RFF 2520	25	1/2"	35	40	47	45	15	13	5	11	72
RFF 2525	25	3/4"	35	40	48	44	16	12	5	11	76




ARTÍCULO	d	Rp	D	D ₁	D ₂	I ₁	I ₂	I ₃	PESO (g)
RFF 3225	32	3/4"	44	42	48	12	17	21	82
RFF 3232	32	1"	45	50	55	13	14	17	124

ACCESORIOS CON ROSCA THREADED FITTINGS

ESPECIFICACIONES TÉCNICAS

TECHNICAL SPECIFICATIONS



ARTÍCULO	d	Rp	D	D ₁	D ₂	l	l ₁	L	PESO (g)
RFF 4040	40	1"1/4"	55	69	52	38	26	78	396
RFF 5050	50	1"1/2"	68	77	58	39	27	84	494
RFF 6363	63	2"	85	93	70	42	30	91	634
RFF 7575	75	2"1/2"	100	118	94	36	32	90	1144
RFF 9090	90	3"	115	135	100	46	35	100	1500
RFF110110	110	4"	140	155	123	44	40	115	1942

Todos los accesorios TORO 25 son compatibles con todas las series de tubos TORO 25.
All TORO 25 pipe fittings are compatible with all TORO 25 pipe series.

NSF 61 approved

STANDARDS:

- ISO 15874
- ISO 15494
- DIN 8077-78