



DРИPPING PIPE WITH FAST WATER JETS DРИPPING DEVICE

Cylindric pipe in polyethylene of high quality with fast water jets dripping devices. The ATP dripping device is composed of large section holes which, thanks to fast water jets, reduce the risk of occlusion. Pressure losses are reduced thanks to the smoothness and thickness of its partition. Moreover the dripping device is easy to clean and that makes it suitable for long-distance use.

TECHNICAL CHARACTERISTICS

- For both diameters and for each spacing the models available are: Normal with 2 holes for water jets and Double with 4 holes for water jets.
- The ATP dripping device is symmetrical, patented and designed to fit in the pipe and to prevent it from coming off and breaking.
- High resistance to occlusion

ADVANTAGES AND APPLICATIONS

- Highly resistant to abrasion, crushing, and mechanical stress during and after installation.
- Increased yield quality and quantity thanks to a constant water supply calculated according to the plant's needs.
- Water and fertilizer savings, with the percentage of use precisely calculated based on the dripper capacity.
- Suitable for: multi-year irrigation systems, open field and greenhouse installations, vegetables and fruit, tree crops, floriculture, gardening, irrigation of gently sloping terrain, fertirrigation, sub-irrigation and impulse irrigation.





TECHNICAL DATA

∅ Nominal		Wall thickness		Flow Rate		Operating Pressure				Filtering	
						min		suggested			
mm	inch	mm	inch	lph	gph	bar	psi	bar	psi	mesh	
16	1/2"	1,1	0,04	2,0	0,53	1	15	1,5	22	29	130
				4,0	1,06						
20	5/8"	1,3	0,05	2,0	0,53	1	15	1,5	22	29	130
				4,0	1,06						



MAXIMUM LENGTH SUGGESTED (m)

∅	Spacing (cm)						
	20	30	40	50	60	75	100
	2 lph - 0,53 gph						
16	75	95	115	130	150	180	200
	4 lph - 1,06 gph						
1/2"	45	60	70	80	90	100	120

∅	Spacing (cm)						
	20	30	40	50	60	75	100
	2 lph - 0,53 gph						
20	100	130	160	180	200	260	280
	4 lph - 1,06 gph						
5/8"	60	75	90	105	120	150	160

PACKAGING

			STANDARD PACKAGING LOAD						NOT STANDARD	
∅	Thickness	Roll lenght	Pallet 41x41x47 inch 105x105x120 cm		Container 20"	Container 40"	TIR 14 m	Roll lenght		
mm	inch	mm	m	ft	rotoli/rolls	rotoli/rolls	rotoli/rolls	m		
16	1,1	0,04	400	1312	-	120	400	450	200-100-50-25	
20	1,3	0,05	300	984	-	100	350	400	150-100-50-25	



CERTIFIED PRODUCT ISO 9261